



**POWER
FLUIDITY
DURABILITY**

**20 Yd³
25 Yd³
29 Yd³
32 Yd³**



**REAR LOADER
SPRINTER**

CHAGNON





THE DURABAC ADVANTAGE

Additional features & options



Centralized junction box.



Tilgate locking system



3 1/2 " x 5 " bore with chrome rod easily replaceable cylinders (4x)



Body attachment to the chassis



Security switch when opening the access door



Safety prop for maintenance



Stainless steel piping



Fast idle engine speed automatically engaged



Retractable ladder



Nylatron and UHMV wear pads on all carrier tracks are accessible from the inside of the packer body and replacable in under 2 hours



Single or dual Duralift Cart Tipper available with American or European grip



Reversible footstep



Available with compressed natural gas (CNG) side and roof mounted tanks



Steerable lift axle



- 14 000 lb hydraulic. Reeving cylinder for commercial containers
- Handle extension
- Kick-bar for 1 to 3 y³ containers (capacity 1500 lb)
- (2) flashing lights located on top of the tailgate / separated switch
- (1 or 2) strobe light with cage located on the tailgate, street side (and/or sidewalk)
- One work light on each side of the body (central position). D.E.L. 1000 lumens
- Side direction lights on each side at mid-body
- Warning light and sound alarm in the cab when the tailgate is raised
- Pump installation directly on transmission PTO, FEPTO or REPTO
- Additional lever on street side
- Hopper floor liners (3) interchangeable plates of QT-400 in 3/16"
- Multiple available camera systems
- Spill kit and holder
- Fire extinguisher kit (10 or 20lbs), canvas and support
- Aluminium side guards
- Pinch point screen mesh protection located on tailgate beside the handle (MOL Ontario)
- Safety switch (palm switch)
- Central lubrication block for easy daily maintenance
- Aluminum or steel toolbox
- Splash plate in front of the body
- Extended warranty




Specifications



MODELS	SPR 20	SPR 25	SPR 29	SPR 32
Capacity (yd ³)	20 yd ³	25 yd ³	29 yd ³	32 yd ³
Unit weight	15,313 lb	15,926 lb	16,160 lb	17,028 lb
BODY				
Body Floor	3/16" (4,.76 mm) 100 000 PSI (single piece, curved).			
Body Side Walls	1/8" (3,.17 mm) 180 000 PSI			
Body Roof	1/8" (3,.17 mm) 180 000 PSI			
Longitudinal reinforcements	10 GA			
Horizontal side post	1/8" (3,17 mm) 44 000 PSI.			
Access door	Driver side			
TAILGATE				
Capacity (yd ³)	3 yd ³			
Hopper floor	5/16" (6.35 mm) 180 000 PSI ..			
Wall exposed section	3/16" (4.76 mm) 100 000 PSI.			
Non-exposed section:	10 Gauge 44 000 PSI.			
Carrier plate rail	1/4" (6,35 mm) 100 000 PSI, with replaceable wear UHMW shoes.			
Removable cover	1/16" (1.587 mm) 14 gauge.			
Side reinforcement	3/16" 44 000 PSI (single sheet) fully welded with drain holes (Hi tensile)			
Tailgate "P" seal	80" height			
Tailgate latch	Auto-locking system.			
Hopper capacity:	3 yd ³			
HYDRAULIC SYSTEM				
Pump	Vanepump			
Installation type	P.T.O.			
Pump capacity	38gpm @1,200 rpm			
Tank	80 gal.			
Operating Pressure	2700 PSI			
Ejection/Tailgate control	Front of body/street side			

PACKER PLATE	
Cylinder bracket	1/2" (12.70 mm) 100 000 PSI.
Packing face	1/4" (6.35 mm) 100 000 PSI.
Hydraulic cylinder	3 1/2" x 5" (127 mm) Bore with chrome rod.
Blade bearing:	2" (50.8 mm) Aluminium bronze.
CARRIER PLATE	
Face plate	3/16" (4,76 mm) 100 000 PSI.
Cylinder bracket	1/2" (12,70 mm) 100 000 PSI.
Hydraulic cylinder	3 1/2" x 5" (127 mm) Bore with chrome rod.
EJECTOR PANEL	
Front	3/16" (4.76mm) 100 000 PSI.
Hydraulic cylinder	Télescopique chrome rod
Wear pad	8 Replaceable UHMW 2"- Nylatron
Ejector track	11/4" 44 000 PSI fully welded
Reinforcement	4" Channel (101.6mm) 44 000 PSI.
Hydraulic cylinder	Nitrated telescopic
ELECTRIC SYSTEM	
Compliance	All LED; FMWSS/CMVSS compliant.
Layout	2 Turn & stop light above hopper each side.1 1 Turn & stop light bellow hopper each side.1 1 License plate light above hopper. 1 Turn signal on half body each side.
PERFORMANCES	
Cycle time	22 seconds
Compaction rate	Std. cyl . compaction rate 1,000 lb (454 Kg)/Y ³
FINISH	
Paint colour	Standard white. Sandblasted, epoxy primed with two (2) coats of acrylic enamel finish, high quality polyurethane.



SPRINTER	20	25	29	32
A Body length	247"	269"	286"	308"
B Recommended CA	144"	164"	184"	201"
C Body height	99 1/4"			
D Overall height	122 1/2"			
E Overall width	102"			
F Hopper width (inside)	80"			
G Hopper opening height	41 1/4"			